



PRODUCT: - NYLON FABRIC SINGLE TEXTURE BOTH SIDE NEOPRENE RUBBER COATED FABRIC TECHNICAL DATA SHEET



TECHNICAL SPECIFICATION

SR NO	PROPERTY	UNIT	STANDARDS	SPECIFICATION
1	Product Code	BAFFLE WALL COATED FABRIC
2	Coated Fabric Thickness	MM	IS 7016 - PART I	0.60 ± 0.05
3	Coated Fabric GSM	Gram/sq. meter	IS 7016 - PART I	600 ± 50
4	Coated Fabric Width	CMS OR MM	IS 7016 - PART I	130
5	BREAKING STRENGTH			
A)	Warp	Kg/50mm	IS 7016 - PART II	170
B)	Weft	Kg/50mm	IS 7016 - PART II	170
6	ELONGATION AT BREAK			
A)	Warp	Kg/50mm	IS 7016 - PART II	30 ± 4
B)	Weft	Kg/50mm	IS 7016 - PART II	30 ± 4
7	TEAR STRENGTH			
A)	Warp	Kg/50mm	IS 7016 - PART III	6
B)	Weft	Kg/50mm	IS 7016 - PART III	6
8	PEEL SARENGTH			
A)	Warp	Kg/50mm	IS 7016 - PART V	5 KG
B)	Weft	Kg/50mm	IS 7016 - PART V	5 KG
9	Colour		As Per Required	As Per Customer Requirement
10	Air Leak Test	Gms/Cm2	As Per Required	When tested at a pressure of 200 gms/cm2 - no leakage found
11	Polymer	..	As Per Required	Neoprene Rubber

Note: All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.*

