

## HIGH ABRASION RESISTANT RUBBER SHEETS

### HIGH ABRASION RESISTANT RUBBER SHEETS

Code	Specific Gravity	Hardness (±5)	Tensile Strength	Elongation at break	Abrasion Resistant	Compression Set at 70°C for 22 hrs	Temp. Range	Color
	gm / cm <sup>3</sup>	Shore A	(min) kg / cm <sup>2</sup>	(min) %	mm <sup>3</sup> 10N	%	°C	
<b>Abrasuper-40</b>	0.98	38 ± 4	240	810	120	15	-30 to +70	Pink/Blue/Orange
<b>Abrasuper-60</b>	1.10	60	200	500	110	15	-30 to +70	Pink/Blue/Orange
<b>ABRA R 60</b>	1.10	60	270	700	110	20	-40 to +70	Red
<b>ABRA HD 60</b>	1.10	60	215	470	110	20	-40 to +75	Black
<b>ABRA HDR</b>	1.15	70	225	600	110	25	-40 to +75	Red
<b>ABRA HD 70</b>	1.15	70	215	450	90	25	-40 to +75	Black

Quality Rubber Solutions

Copyright © 2017 \*| Zenith Industrial Rubber Products Pvt Ltd |\*, All rights reserved.

**Our mailing address is**

[info@zenithrubber.com](mailto:info@zenithrubber.com) (International) | [sales@zenithrubber.com](mailto:sales@zenithrubber.com) (Domestic)



**Zenith Industrial Rubber Products Pvt Ltd**

141/144, Free Press House, Nariman Point, Mumbai, India - 400021, Ph- +91 (22) 6143 6500